



CARACTÉRISTIQUES TECHNIQUES

OUTDOOR UNIT		COLI09D8SHC	COLI12D8SHC
Cool capacity	kW	2.64 (1.03-3.22)	3.50(1.38~4.31)
Heating capacity	kW	2.90 (0.82-3.37)	3.90(1.07~4.38)
P design capacity cooling	kW	2,64	3,50
P design capacity heating(warmer)	kW	2,70	3,10
P design capacity heating(average)	kW	2,40	2,60
Temp range cooling	°C	-15~50	-15~50
Temp range heating	°C	-15~24	-15~24
SEER / SCOP(warmer) / SCOP(average)	W/W	8.8 / 6.0 / 4.6	8.5 / 6.0 / 4.6
Energy label		A+++ / A+++ / A++	A+++ / A+++ / A++
Yearly energy consumption	kWh	105 / 630 / 730	144 / 723 / 791
EER/COP	W/W	4.19 / 4.46	3.60 / 3.90
Voltage, Hz		220-240V~, 50Hz	220-240V~, 50Hz
Standard current (cooling)	A	2,75	4,25
Standard input (cooling)	W	630	970
Standard current (heating)	A	2,85	4,35
Standard input (heating)	W	650	1000
Rated current	A	10,5	10,5
Rated input	W	2200	2200
Refrigerant amount	kg	0,62	0,62
Compressor model		KSN98D64UFZ3	KSN98D64UFZ3
Refrigerant oil/oil quantity	ml	ESTER OIL RB74AF 300	ESTER OIL RB74AF 300
Liquid side/Gas side	mm(inch)	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35/Φ9.52 (1/4"/3/8")
Standard piping length	m	5	5
Min piping length	m	3	3
Max piping length	m	25	25
Max difference	m	10	10
Additional charge	g/m	12	12

INDOOR UNIT		COLI09D8SHF	COLI12D8SHF
Indoor fan motor Input	W	20	20
Indoor fan motor max current	A	0,5	0,5
Sound power level	dB(A)	55	56
Sound pressure level (Min. ~ Max.)	dB(A)	19~37	21~39
Air flow(Min. ~ Max.)	m³/h	160~560	170~630
Weight (Net/Gross)	kg	8.7/11.5	8.7/11.3
Dimensions (W×D×H)	mm	835×208×295	835×208×295
Packing (W×D×H)	mm	905×290×355	905×290×355

OUTDOOR UNIT		COLI09D8SHC	COLI12D8SHC
Sound power level	dB(A)	59	62
Sound pressure level	dB(A)	54	54,5
Airflow	m³/h	2150	2200
Weight (Net/Gross)	kg	26.7/29.1	26.7/29.1
Dimensions (W×D×H)	mm	765×303×555	765×303×555
Packing (W×D×H)	mm	887×337×610	887×337×610

FONCTIONS

- ✓ AFFICHAGE LED ON/OFF
- ✓ FILTRATION ANTI-ACARIEN
- ✓ 3 VITESSES DE VENTILATION
- ✓ ECONOMIE D'ENERGIE
- ✓ 3 MODES : SILENCE | CLEAN | TIMER
- ✓ FONCTION DE DÉSHUMIDIFICATION



COMMANDES



Télécommande



Commande filaire
(option)



Commande Wi-fi
Clef non fournis
(option)